


Metropolis Technical Specification





1- The coloured panels are made with a compact material 13mm thick. It is made up of 70% of softwood fibres and 30% of thermosetting resin, and it stands up to weathering very well (sun, rain, damp, etc.). The coloured surfaces are treated with products based on coloured acrylic polyurethane resins; this enables them to stand up well to UV radiation and resist damage.



- 2- The 125mm diameter posts and the 95mm square posts are made of lacquered galvanised steel. The two-tone grey graining finish has a slightly undulating surface for increased scratch resistance.

 The same are made of injection moulded polyamide.
 - The caps are made of injection moulded polyamide.
- **3- The platforms** are made from a 12.5mm thick, textured, non-slip compact material (HPL).
- 4- The tubes are made of stainless steel, diameter 40mm, guaranteeing lasting durability and reliability of the equipment.
 Injection moulded polyamide fixings connect the posts to the platforms and the various play features.
- 5- The tubular slide is made of rotary moulded polyethylene.
- **6- The climbing holds** are made of injected polyamide, combining rigidity and sturdiness.



- 7- The "Kayak" slide is made of rotary moulded polyethylene.
- **8-** The steps of the catwalk are made with a non-slip rubber overmould.
- **9- The gangway floor** is made of solid wood planks, with rubber elements between the planks to avoid all risk of catching a finger.
- 10- The stainless steel fixings are protected by polyamide anti-vandalism caps.















